

ACCESSIBLE LIFTS COMPLIANT WITH EN81-70:2018

We offer a range of solutions for ensuring compliance with various codes and regulations, including accessibility, vandal resistance, and operation during a fire. This factsheet gives an overview of the main requirements introduced in the new EN81-70:2018 European standard.

The EN81-70 standard defines lift controls, distances, dimensions, contrasts and accessories that facilitate access for people using wheelchairs or walking aids. KONE EcoSpace®, KONE MonoSpace® 500, KONE MonoSpace® 700, KONE TranSys™ and KONE MiniSpace™ lifts are all available with EN81-70:2018 compliance.

FUNDAMENTAL REQUIREMENTS

The EN81-70:2018 standard introduces requirements for lift car size and interiors:

- A handrail must be installed in the lift car on the side of the car operating panel (COP)
 - If the distance between the COP and the adjacent corner is less than enabling 400 mm handrail fit on wall, then a handrail must be installed on both sides of the COP
 - For car types 1, 2, and 3 (please see table 1) the handrail can be installed on the wall opposite the COP, if the front wall width is less than the depth of the handrail
 - For car types 4 and 5 the second handrail must be installed on the wall opposite the COP or on the back wall.
- A mirror is mandatory for car types 1, 2 and 3
- Decorative finishes must not reduce the nominal car depth and width of each car type by more than 15 mm on each wall.
 - There shall be no additional features attached to the car walls below a height of 800 mm which may restrict the accommodation and turning of passengers using wheelchairs or passengers with other walking aids. This

would particularly be the case for type 1 and type 2 cars restricting the minimum depth and for type 4 cars restricting the smaller minimum dimension. In some cases it may be necessary to increase the nominal car width or depth by a few mm, depending on wall finishing used, to compensate the extra space needed.

- Signalisation related requirements
 - The audible signal strength must be adjustable between 35 and 65 dB(A) for car environments. In noisy environments, the sound level should be adjustable up to 80 dB(A).
 - A 30% contrast is required:
 - from push button to faceplate or immediate surroundings
 - symbol on push button to the background of button
 - faceplate to its surroundings on landing
 - there is no luminance contrast requirement for devices mounted on the doorframe
 - there is no luminance contrast requirement between the COP and the faceplate when the COP contains five (5) or more buttons

CAR TYPE	MINIMUM CAR WIDTH (mm)	MINIMUM CAR DEPTH (mm)	MINIMUM CLEAR OPENING WIDTH (mm)
1	1000	1300	800
2	1100	1400	900
3	1100	2100	900
4	1600 or	1400	900
	1400	1600	900
5	2000 or	1400	1100
	1400	2000	1100

Table 1: Car types and dimensions



EN 81-70-2003 compliant landing call station



EN 81-70-2018 compliant landing call station