



implementable signaling devices		
position	device	symbol
A	push button, 4 x 0.34mm ²	
A	domed push button, 4 x 0.34mm ²	
A	push button 2-positions, 4 x 0.34mm ²	
A	key switch, 4 x 0.34mm ²	
A	pull switch, 4 x 0.34mm ²	
A	elbow push switch, 4 x 0.34mm ²	
A	PGS wired UTP Cat5, 8 wires Ø0,5mm	
B	wall socket: 230V. 3 x 2.5mm ²	
C	photocell incl. cable	
D	motion sensor incl. cable	

other implementable electrical devices	
INPUT:	- intercom
	- fire alarm system
potential free contact switch	
OUTPUT:	- bel switch
	- alarm system
I _{max.} = 400mA	

Glass measurements in m		
	WIDTH	HEIGHT
	1215	2375

Title: A3 overview		Copyright by Kone
Order number: KONE Sliding Door 00-0711_Glass - single	Page 00-0711	Projection ISO-128
Date: 24-huhti-18	Scale: --	REV.NO.:
Drawn by: Tekenaar	Paper size: A3	A: --
		B: --
		C: --
Accustraat 21 Postbus 94 3900 AB Veenendaal tel. : 0318 - 532333 fax : 0318 - 532339		