



implementable signaling devices		
position	device	symbol
A	push button, 4 x 0.34mm ²	
A	domed push button, 4 x 0.34mm ²	
A	push button 2-positions, 4 x 0.34mm ²	
A	key switch, 4 x 0.34mm ²	
A	pull switch, 4 x 0.34mm ²	
A	elbow push switch, 4 x 0.34mm ²	
A	PGS wired UTP Cat5, 8 wires Ø0,5mm	
B	wall socket: 230V. 3 x 2.5mm ²	
C	photocell incl. cable	
D	motion sensor incl. cable	

other implementable electrical devices	
INPUT:	- intercom
	- fire alarm system
	potential free contact switch
OUTPUT:	- bel switch 24V
	- alarm system 24V
	I _{max.} = 400mA

Glass measurements in mm		
	WIDTH	HEIGHT
LEFT DOORWING	886	2202
RIGHT DOORWING	886	2202

Title: W35S_Kone SD-D		Copyright by Kone	
Order number:	Page no:06	Projection ISO-128	
Date: .	Scale: --	A	
Drawn by:	Paper size: A3		
		Accustraat 21 Postbus 94 3900 AB Veenendaal tel. : 0318 - 532333 fax : 0318 - 532339	
		REV.NO.: A: -- B: -- C: --	