



implementable signaling devices		
position	device	symbol
A	push button, 4 x 0.34mm²	
A	domed push button, 4 x 0.34mm²	
A	push button 2-positions, 4 x 0.34mm²	
A	key switch, 4 x 0.34mm²	
A	pull switch, 4 x 0.34mm²	
A	elbow push switch, 4 x 0.34mm²	
A	PGS wired UTP Cat5, 8 wires Ø0,5mm	
B	wall socket: 230V. 3 x 2.5mm²	
C	photocell incl. cable	
D	motion sensor incl. cable	

other implementable electrical devices	
INPUT:	- intercom
	- fire alarm system
	potential free contact switch
OUTPUT:	- bel switch  24V
	- alarm system  24V
	I <sub>max.</sub> = 400mA

Glass measurements in mm		
	WIDTH	HEIGHT
LEFT DOORWING	886	2202
RIGHT DOORWING	886	2202

Title: KONE SD65 SD-D RW		Copyright by Kone
Order number: KONE Sliding Door SD65	Page 5 of 6	Projection ISO-128
Date: 24-huhti-18	Scale: --	REV.NO.:
Drawn by: Tekenaar	Paper size: A3	A: --
		B: --
		C: --
		Accustraat 21 Postbus 94 3900 AB Veenendaal tel. : 0318 - 532333 fax : 0318 - 532339